



The LF BP1015 includes a 15" low frequency woofer with a 100 mm voice coil. The cabinet is internally stiffened by rugged reinforcements. The enclosure is constructed with 18 mm Finnish birch. It is finished in black textured semi-matt. Two speakon® NL4MPR connectors provide input and loop through connection.

Technical specifications

| | |
|-------------------------------------|---|
| Sensitivity ⁽¹⁾ : | 95 dB spl @ 1m/W |
| Frequency response ⁽²⁾ : | 35 Hz to 180 Hz |
| Program power: | 1000W |
| Continuous power rating: | 500W |
| Maximum sound pressure: | 123 dB spl @ 1m |
| Power compression: | Less than 3 dB |
| Impedance: | 8 Ohms |
| Dimension (W x H x D): | 50,0 cm x 50,0 cm x 40,0 cm |
| Weight: | 24 Kg |
| Connectors: | 2 x Neutrik NL4FC (+1/-1) |
| Drivers: | 15" LF driver with 100 mm voice coil |
| Finish: | Black scratch resistant waterborne coating system |

(1). Sensitivity is based on a swept 100 Hz to 500 Hz signal for an input of 2,83 V @ 8 ohms or 2,0 V @ 4 ohms

(2). Frequency range is defined as the frequency extremes where the response is -10dB from the rated sensitivity

